



T-YARIK FREZE, ÇAPRAZ DİŞLİ DIN850

D h12	S e 8	L	d h6	Z	bxh DIN 6888
10,5	2	50	12	6	2x3,7
10,5	2,5	50	12	6	2,5x3,7
10,5	3	50	12	6	3x3,7
13,5	2	56	12	6	-
13,5	3	56	12	6	3x5
13,5	4	56	12	6	4x5
16,5	2	56	12	6	3x6,5
16,5	3	56	12	6	3x6,5
16,5	4	56	12	6	4x6,5
16,5	5	56	12	6	5x6,5
19,5	3	56	12	8	-
19,5	4	56	12	8	4x7,5
19,5	5	56	12	8	5x7,5
19,5	6	56	12	8	6x7,5
22,5	4	56	12	8	-
22,5	5	63	12	8	5x9
22,5	6	63	12	8	6x9
22,5	8	63	12	8	8x9
25,5	5	63	12	10	-
25,5	6	63	12	10	6x10
28,5	6	63	12	10	6x11
28,5	8	63	12	10	8x11
28,5	10	71	12	10	10x11
32,5	6	71	12	10	-
32,5	7	71	12	10	-
32,5	8	71	12	10	8x13
32,5	10	71	12	10	10x13
38,5	8	71	12	10	-
45,5	8	71	12	12	-
45,5	10	71	12	12	10x16

HSS → Yüksek hız çeliği

KULLANIM ALANI

- 800 N/mm² mukavemetindeki alaşımlı dövme çelikler
- Takım çelikleri
- Döküm alaşımlı malzemeler
- Kama yuvalarının açılmasında