



ÜÇGEN 60° NEGATİF

TN

	Boyutlar (mm)		
Ölçü	d	t	d1
11	6.35	3.18	2.40
16	9.525	4.76	3.81
22	12.7	4.76	5.16
27	15.875	6.35	6.35
33	19.05	9.52	7.93

İş Parçası	Çelik	P	●	●	○	○									●	●	●	●	●	●	●	●			Açıklama	
	Paslanmaz çelik	M	○	○	●	●																●				
	Dökme demir	K						●	●	●	●	●													●	Önerilir
	Demir-dışı metaller	N																							○	Kabul Edilebilir
	Isı dayanımlı alaşımlar, titanyum alaşımları	S				○	●	●	●																	○
Sertleştirilmiş Çelik	H					●	●	●																		

Kesici Uç	Kod	Kaplama																		Kaplama		Kesme Koşulları					
		KR1020	KR1025	KR1220	KR1225	KR1305	KR1320	KR1325	KR3105	KR3115	KR3125	KR3215	KR3225	KR4025	KR4035	KR4125	KR4135	KR4225	KR4235	KR4245	KR4340	KR001	KR101	f _n (mm/dev)	a _p (mm)		
	TNMG	110308-TM																							0.15~0.42	0.50~3.50	
		160404-TM		●			●	●	●						●		●		●							0.10~0.40	0.40~3.50
		160408-TM		●		●	●		●						●		●		●							0.15~0.45	0.50~4.00
		160412-TM							●						●		●									0.15~0.50	0.80~4.50
		160416-TM																								0.18~0.50	1.00~4.50
		220404-TM																								0.10~0.35	0.40~5.00
		220408-TM																								0.15~0.45	0.50~5.50
		220412-TM																								0.15~0.50	0.80~6.00
		220416-TM																								0.20~0.55	1.00~6.00
		270612-TM																								0.28~0.60	1.20~8.00
330924-TM																								0.35~0.70	2.30~13.00		