



ÜNİVERSAL TORNA AYNALARA SİRALLİ



KOD	Ø	A
TOS.SPR.	80	30
TOS.SPR.	100	40
TOS.SPR.	125	50
TOS.SPR.	160	84
TOS.SPR.	200	100
TOS.SPR.	250	132
TOS.SPR.	315	168
TOS.SPR.	400	225
TOS.SPR.	500	270

ÜNİVERSAL TORNA AYNALARI SIKMA KAPASİTELERİ



Ø	E	F	G	H	J	K	L	N	O	P	R	S max.	T max.
80	3-27	-	23-48	48-73	-	-	3-27	27-51	52-76	-	-	98	-
100	3-39	3-45	24-60	58-94	25-67	60-102	3-39	30-66	64-100	42-72	77-107	122	130
125	3-49	3-47	30-75	70-116	28-74	69-115	3-49	38-84	83-125	50-95	90-136	152	163
160	3-76	3-76	46-119	87-160	35-108	91-166	3-76	50-123	91-164	51-128	109-185	208	218
200	5-88	5-83	56-140	116-200	46-125	105-185	5-88	57-140	117-200	69-148	127-207	246	254
250	5-107	5-125	68-162	156-250	60-183	124-247	5-107	66-168	154-256	83-206	147-270	314	328
315	8-136	8-131	74-201	188-315	65-193	145-273	8-131	79-207	193-321	99-225	174-305	392	382
400	10-187	10-187	90-268	223-400	105-282	173-350	10-187	92-274	224-406	118-290	189-358	498	454
500	25-250	25-250	135-360	275-500	135-411	201-477	25-250	135-360	275-500	125-447	191-513	626	579

ÜNİVERSAL TORNA AYNALARI SALGI DEĞERLERİ

